

## MOUNTING OPTIONS

2/90 Sign Systems offers numerous standard mounting options to meet a variety of installation applications.

- A Pressure Sensitive** – Pressure sensitive mounting intended for smooth, hard surfaces. Not recommended for selected vinyl wall coverings. Can be used with silastic bonding. 100 square inches maximum.
- B Magnetic** – Same as “A” but uses magnetic mounting for steel surfaces. 100 square inches maximum.
- C Velcro** – Same as “A” but uses Velcro<sup>®</sup> for fabric surfaces. 100 square inches maximum.
- D Screw-on** – Screw-on mounting for rough surfaces such as brick and drywall, where “A” is not recommended. Recommended on all wall mounted signs larger than 100 square inches.
- E Pin** – A specifically designed pin device for fabric surfaces. Unique one piece design enables mounting to any fabric surface including fabrics mounted over hard materials. 100 square inches maximum.
- F Hook** – Hook device in clear plastic which “hooks over” top of panel. Automatically locates sign two inches from top of panel. **Order must specify panel make and thickness.**
- G Freestanding** – For freestanding applications such as receptionist name signs. Extruded aluminum bracket. **Maximum sign height of 4” for standard and 2” for Thin is recommended. 2/90 Thin stand sits at 30° angle.**
- H Panel Top** – For mounting on top surface of panel. Extruded aluminum bracket with pressure sensitive tape. **Maximum sign height of 8” is recommended.**
- I Ceiling Mount (Suspended Ceiling)** – Connects to grid system using extruded aluminum 2” brackets. Signs appear to be “floating” below ceiling line. **Specify 1/2” or 1” grid system.**
- J Ceiling Mount (Hanging)** – General purpose hanging applications for high or irregular ceilings. Hang lines tie to various points (rafters, beams, duct work, piping, etc.) Customer must supply hanging line material.
- K Perpendicular Wall Mount** – Mounts sign at 90° angle to wall surface. **Not available on signs wider than 15”.**
- L Inside of Glass Mount** – Clear acrylic bracket attached to glass with clear pressure sensitive tape.
- M Ceiling Mount (Hanging)** – Extruded aluminum bracket screw mount. No mounting screws provided with this mount.
- N Ceiling Mount (Rigid Post)** – Sign mounts 6, 12, 18 or 24 inches from ceiling using 1/2” black aluminum rod.
- O Flexible Panel Mount** – Under the top cap panel device in black or white fabric. Automatically locates the sign flush with the top of the panel. **Order must specify fabric color.**
- P Panel and Tile Mount** – Hook device in aluminum which hooks over the top of panel, under the top cap. Automatically locates sign flush with the top of the panel. **Order must specify panel make and thickness.**

\*Not available for 2/90 Thin. Additional mounting solutions available.

**CUSTOMER IS RESPONSIBLE FOR SUITABILITY OF EACH MOUNTING OPTION.  
 TESTING IS RECOMMENDED PRIOR TO USE.**